



ST1010V4F


◆ 自动门襟机 ◆

Automatic J-stitch Machine

SCAN HERE TO SEE OPERATION VIDEO



扫描二维码观看操作视频



采用缝料直驱系列PLK2516R全旋梭花样机头，适用于牛仔面料，斜纹裤子的门襟J型线自动车缝工序，双倍大旋梭梭床。With Sewtech PLK2516R direct drive rotary hook sewing head, it is high speed, robust and durable. Target to denim materials, twill materials, applicable for jeans/pants front fly J-stitch operation, double rotary hook.

技术参数(Tech & Parameters) :

最大转速/Max speed: 2800 RPM
锁式线迹/Lock stitch
车缝区域/Max pocket area: 250 x 160mm
花样数据储存量/Pattern quantity in memory: 999 + USB memory
产品计数/work piece counter: 上/下计数/up/down (0-9999)

缝距/stitch length: 0.1-12.7mm

断线感应/thread breakage detect

自动送料, 自动收料/ Automatic feeding, automatic collecting

用电/power & consumption: 220V 1P 50/60Hz, 1.25Kw (direct drive)

用气/Air pressure: 5 Bar

生产效率/Efficiency: 每分钟约6-8条裤子/ 6-8 J-stitch per minute

归类(Category) :

牛仔斜纹裤压门襟线, 中厚料, 裤子
jeans, twill materials J-stitching.

选型/Model:

基本型: ST1010V4F, 单针自动压门襟线机
Basic Model: ST1010V4F, Single Needle
J-stitch machine

SCAN HERE TO SEE OPERATION VIDEO




扫描二维码观看操作视频

ST9588

◆ 高速埋夹机 ◆

Feed-Off-The-Arm Machine with integrated Puller



工艺: 合缝



自动抬压脚, 气动抬推轮, 自动机针冷却, 自动剪线装置, 线头吸入式;
内置电子拖布轮, 轻松处理弹性面料;
上轴全自动供油

Pressure Foot Auto-lift, Automatic Puller lift, Needle air cooler,

Automatic thread trimming, thread hold by vacuum;

Automatic Belt Puller, suitable for even elastic materials;

Automatic lubricating upper shaft.

技术参数(Tech & Parameters):

链式线迹/Double Chain stitch

最高缝速/Max Speed/ 4300RPM

缝距Stitch Length/2.6-4.8mm

机针间距 Needle/2 or 3 needles; needle gauge: 6.4mm

马达电控 Motor and Control Box/Hoshing Full Function Control and Servo Motor